



MATERIAL SAFETY DATA SHEET  
CLC LUBRICANTS

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:	CLC Lube MO 5, MO 10, MO 20, MO 25, MO 30, MO 40, MO 45, MO 50, MO 60
CHEMICAL NAME:	Mixture
DOT SHIPPING NAME:	N/A
SARA TITLE III SECTION 313:	N/A
MANUFACTURER	EMERGENCY TELEPHONE NUMBER
CLC LUBRICANTS	INFOTRAC: 1-800-535-5053
100 S. Old Kirk Road	
P.O. Box 764	HMIS RATING: 1-1-0
Geneva, IL 60134	
Telephone (630) 232-7900	

2. COMPOSITION

Hydrotreated Petroleum Oil	TLV - 5 mg/M3 OSHA TWA/ACGIH TWA
CAS# 64742-52-5	(Oil Mist)

3. EMERGENCY AND FIRST AID PROCEDURES

Eye Contact: Flush with water for 15 minutes. If irritation persists, seek medical attention.

Skin Contact: Wash with soap and water. If irritation occurs, seek medical attention.

Inhalation: Remove to fresh air. If breathing difficulties arise, seek medical attention.

Ingestion: Consult a Physician.

4. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (deg F)	Above 400	Specific Gravity (water = 1)	LIGHTER
Solubility in Water	NEGLIGIBLE	Evaporation Rate (ether = 1)	SLOWER
Percent Volatile	NEGLIGIBLE	Vapor Density	N/D
Appearance	YELLOW TO AMBER LIQUIDS	Odor	MILD

5. EFFECTS OF OVEREXPOSURE

Eyes: May result in mild eye irritation.

Skin: Prolonged or repeated contact with skin may result in irritation.

Inhalation: Inhalation of high vapor concentrations evolved at elevated temperatures may result in respiratory irritation.

Ingestion: May result in gastrointestinal irritation.

6. SPECIAL PROTECTION INFORMATION



MATERIAL SAFETY DATA SHEET  
CLC LUBRICANTS

Respiration Protection: Normally not needed if TLV is not exceeded.

Ventilation: Sufficient to satisfy TLV.

Protective Gloves: Oil resistant.

Eye Protection: Safety glasses to avoid splashing hazard.

7. STABILITY AND REACTIVITY

Stability: STABLE                      Hazardous Polymerization: WILL NOT OCCUR

Incompatibility: STRONG OXIDANTS

Hazardous      Decomposition      Products:              Oxides      of      carbon      and      sulfur

8. SPILL/LEAK/STORAGE PROCEDURES

Precautions in Case of Spill or Release: Prevent entry into sewers or waterways by diking. Absorb small amounts using inert material.

Waste Disposal Method: Assure compliance with applicable federal state and local regulations.

Handling and Storage Precautions: Keep containers closed when not in use. Store away from heat.

9. FIRE FIGHTING MEASURES

Flash Point Range: OVER 200F

Extinguishing Media: Foam, Dry Chemical, Carbon Dioxide

Unusual Fire/Explosion Hazards: Avoid contact with strong oxidants and acids.

Fire Fighting Procedures: Use NIOSH approved supplied-air respirator for confined areas.

The above information is accurate to the best of our knowledge, however it is not warranted to be. Users are advised to confirm that the information is current, applicable and suitable to their circumstances.